

705 UNIVERSAL FAST ADHESIVE ACTIVATOR

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 11/2/2014

Revision date: 1/20/2016

Supersedes: 12/12/2015

Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : 705 UNIVERSAL FAST ADHESIVE ACTIVATOR
Product code : 705
Type of product : Aerosol
Vaporizer : Aerosol
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

AKKİM YAPI KİMYASALLARI SANAYİ ve TİCARET A.Ş.
Yeşilbayır mahallesi Şimşir sokak No:22
34555 İSTANBUL - TURKEY
T +90 2127711371 - F +90 2127713888
info@akfix.com - www.akfix.com

1.4. Emergency telephone number

Emergency number : +90 2127711371 (9:00 am - 17:00 pm GMT+2)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229	On basis of test data
Skin corrosion/irritation, Category 2	H315	Calculation method
Reproductive toxicity, Category 2	H361	Calculation method
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336	Calculation method
Specific target organ toxicity — Repeated exposure, Category 2	H373	Calculation method
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411	Calculation method

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Causes skin irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :





705 UNIVERSAL FAST ADHESIVE ACTIVATOR

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 11/2/2014

Revision date: 1/20/2016

Supersedes: 12/12/2015

Version: 1.1

Signal word (CLP)	: Danger
Hazardous ingredients	: n-hexane; Petroleum gases, liquefied, Petroleum gas, [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately -40 °C to 80 °C (-40 °F to 176 °F).]
Hazard statements (CLP)	: H222 - Extremely flammable aerosol H229 - Pressurised container: May burst if heated H315 - Causes skin irritation H336 - May cause drowsiness or dizziness H361 - Suspected of damaging fertility or the unborn child H373 - May cause damage to organs through prolonged or repeated exposure H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (CLP)	: P102 - Keep out of reach of children P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P211 - Do not spray on an open flame or other ignition source P251 - Do not pierce or burn, even after use P260 - Do not breathe gas, spray, vapours P271 - Use only outdoors or in a well-ventilated area P273 - Avoid release to the environment P280 - Wear eye protection, face protection, protective clothing, protective gloves P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing P308+P313 - IF exposed or concerned: Get medical advice/attention P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste
Child-resistant fastening	: Not applicable
Tactile warning	: Applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-hexane	(CAS No) 110-54-3 (EC no) 203-777-6 (EC index no) 601-037-00-0	50 - 70	Flam. Liq. 2, H225 Repr. 2, H361f Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411
Petroleum gases, liquefied, Petroleum gas, [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately -40 °C to 80 °C (-40 °F to 176 °F).] (Note K)(Note S)(Note U)	(CAS No) 68476-85-7 (EC no) 270-704-2 (EC index no) 649-202-00-6	30 - 40	Press. Gas Flam. Gas 1, H220 Carc. 1A, H350 Muta. 1B, H340
N,N-dimethyl-p-toluidine (Note C)	(CAS No) 99-97-8 (EC no) 202-805-4 (EC index no) 612-056-00-9	0.1 - 1	Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 STOT RE 2, H373 Aquatic Chronic 3, H412

Specific concentration limits:

Name	Product identifier	Specific concentration limits
n-hexane	(CAS No) 110-54-3 (EC no) 203-777-6 (EC index no) 601-037-00-0	(C >= 5) STOT RE 2, H373

705 UNIVERSAL FAST ADHESIVE ACTIVATOR Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 11/2/2014

Revision date: 1/20/2016

Supersedes: 12/12/2015

Version: 1.1

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note K : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-P210-P403 (Table 3.1) or the S-phrases (2-)9-16 (Table 3.2) should apply. This note applies only to certain complex oil-derived substances in Part 3.

Note S : This substance may not require a label according to Article 17 (see section 1.3 of Annex I) (Table 3.1). This substance may not require a label according to Article 23 of Directive 67/548/EEC (see section 8 of Annex VI to that Directive) (Table 3.2).

Note U : When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Recover mechanically the product. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.



705 UNIVERSAL FAST ADHESIVE ACTIVATOR

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 11/2/2014

Revision date: 1/20/2016

Supersedes: 12/12/2015

Version: 1.1

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

705 UNIVERSAL FAST ADHESIVE ACTIVATOR		
Austria	Local name	n-Hexan
Austria	MAK (mg/m ³)	72 mg/m ³
Austria	MAK (ppm)	20 ppm
Austria	MAK Short time value (mg/m ³)	288 mg/m ³
Austria	MAK Short time value (ppm)	80 ppm
Belgium	Local name	n-Hexane
Belgium	Limit value (mg/m ³)	72 mg/m ³
Belgium	Limit value (ppm)	20 ppm
Bulgaria	Local name	n-Хексан*
Bulgaria	OEL TWA (mg/m ³)	72 mg/m ³
Croatia	Local name	n-Heksan
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	72 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	20 ppm
Croatia	Naznake (HR)	EU**, F, Xn, N
Czech Republic	Local name	n-Hexan
Czech Republic	Expoziční limity (PEL) (mg/m ³)	70 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	19.9 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	200 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	57 ppm
Czech Republic	Remark (CZ)	D, P
Denmark	Local name	n-Hexan (2007)
Denmark	Grænseværdie (langvarig) (mg/m ³)	72 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	20 ppm
Denmark	Anmærkninger (DK)	E
Estonia	Local name	n-heksaan
Estonia	OEL TWA (mg/m ³)	72 mg/m ³
Estonia	OEL TWA (ppm)	20 ppm
Finland	Local name	n-Heksaani
Finland	HTP-arvo (8h) (mg/m ³)	72 mg/m ³
Finland	HTP-arvo (8h) (ppm)	20 ppm
France	Local name	n-Hexane
France	VME (mg/m ³)	72 mg/m ³
France	VME (ppm)	20 ppm
Germany	Local name	n-Hexan
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	180 mg/m ³



705 UNIVERSAL FAST ADHESIVE ACTIVATOR

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 11/2/2014

Revision date: 1/20/2016

Supersedes: 12/12/2015

Version: 1.1

Germany	TRGS 900 Occupational exposure limit value (ppm)	50 ppm
Germany	Remark (TRGS 900)	DFG,EU,Y
Greece	OEL TWA (mg/m ³)	72 mg/m ³
Greece	OEL TWA (ppm)	20 ppm
Hungary	Local name	n-HEXÁN
Hungary	AK-érték	72 mg/m ³
Hungary	Megjegyzések (HU)	b, i; II.1.
Ireland	Local name	n-Hexane
Ireland	OEL (8 hours ref) (mg/m ³)	72 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	20 ppm
Ireland	Notes (IE)	IOELV
Italy	Local name	n-Esano
Italy	OEL TWA (mg/m ³)	72 mg/m ³
Italy	OEL TWA (ppm)	20 ppm
Latvia	Local name	n-Heksāns
Latvia	OEL TWA (mg/m ³)	72 mg/m ³
Latvia	OEL TWA (ppm)	20 ppm
Lithuania	Local name	n-heksanas
Lithuania	IPRV (mg/m ³)	72 mg/m ³
Lithuania	IPRV (ppm)	20 ppm
Lithuania	Remark (LT)	R
Luxembourg	Local name	n-Hexane
Luxembourg	OEL TWA (mg/m ³)	72 mg/m ³
Luxembourg	OEL TWA (ppm)	20 ppm
Malta	Local name	n-Hexane
Malta	OEL TWA (mg/m ³)	72 mg/m ³
Malta	OEL TWA (ppm)	20 ppm
Netherlands	Local name	n-Hexaan
Netherlands	Grenswaarde TGG 8H (mg/m ³)	72 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	144 mg/m ³
Poland	Local name	Heksan (n-heksan)
Poland	NDS (mg/m ³)	72 mg/m ³
Portugal	Local name	n-Hexano
Portugal	OEL TWA (ppm)	50 ppm
Romania	Local name	Hexan (n)
Romania	OEL TWA (mg/m ³)	72 mg/m ³
Romania	OEL TWA (ppm)	20 ppm
Slovenia	Local name	n-heksan
Slovenia	OEL TWA (mg/m ³)	72 mg/m ³
Slovenia	OEL TWA (ppm)	20 ppm
Spain	Local name	n-Hexano
Spain	VLA-ED (mg/m ³)	72 mg/m ³
Spain	VLA-ED (ppm)	20 ppm
Spain	Notes	(2007), VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento.), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.)
Sweden	Local name	n-Hexane
Sweden	nivågränsvärde (NVG) (mg/m ³)	90 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	25 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	180 mg/m ³



705 UNIVERSAL FAST ADHESIVE ACTIVATOR

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 11/2/2014

Revision date: 1/20/2016

Supersedes: 12/12/2015

Version: 1.1

Sweden	kortidsvärde (KTV) (ppm)	50 ppm
United Kingdom	Local name	n-Hexane
United Kingdom	WEL TWA (mg/m ³)	72 mg/m ³
United Kingdom	WEL TWA (ppm)	20 ppm
Iceland	Local name	n- Hexan
Iceland	OEL (8 hours ref) (mg/m ³)	72 mg/m ³
Iceland	OEL (8 hours ref) (ppm)	20 ppm
Norway	Local name	n-Heksan
Norway	Grænseverdier (AN) (mg/m ³)	72 mg/m ³
Norway	Grænseverdier (AN) (ppm)	20 ppm
Norway	Merknader (NO)	R
Switzerland	Local name	Hexane (n-Hexane)
Switzerland	VME (mg/m ³)	180 mg/m ³
Switzerland	VME (ppm)	50 ppm
Switzerland	VLE (mg/m ³)	1440 mg/m ³
Switzerland	VLE (ppm)	400 ppm
Switzerland	Remark (CH)	4x15
Australia	Local name	Hexane (n-Hexane)
Australia	TWA (mg/m ³)	72 mg/m ³
Australia	TWA (ppm)	20 ppm
USA - ACGIH	Local name	n-Hexane
USA - ACGIH	ACGIH TWA (ppm)	50 ppm
USA - ACGIH	Remark (ACGIH)	CNS impair; peripheral neuropathy; eye irr; skin; BEI

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Wear respiratory protection
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Liquid under pressure.
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 64 - 72 °C
Flash point	: < 60 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.78 g/cm ³

705 UNIVERSAL FAST ADHESIVE ACTIVATOR Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 11/2/2014

Revision date: 1/20/2016

Supersedes: 12/12/2015

Version: 1.1

Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 89 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
-----------------------	--

Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
--	--------------------------------------

Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
--	--

Aspiration hazard	: Not classified
-------------------	------------------

705 UNIVERSAL FAST ADHESIVE ACTIVATOR

Vaporizer	Aerosol
-----------	---------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

705 UNIVERSAL FAST ADHESIVE ACTIVATOR Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 11/2/2014

Revision date: 1/20/2016

Supersedes: 12/12/2015

Version: 1.1

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1950
UN-No. (IMDG) : 1950
UN-No. (IATA) : 1950
UN-No. (ADN) : 1950
UN-No. (RID) : 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, flammable
Proper Shipping Name (ADN) : AEROSOLS
Proper Shipping Name (RID) : AEROSOLS
Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS
Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS
Transport document description (ADN) : UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
Transport document description (RID) : UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 2.1
Danger labels (ADR) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1

705 UNIVERSAL FAST ADHESIVE ACTIVATOR Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 11/2/2014

Revision date: 1/20/2016

Supersedes: 12/12/2015

Version: 1.1

Hazard labels (IATA) : 2.1



ADN

Transport hazard class(es) (ADN) : 2.1

Danger labels (ADN) : 2.1



RID

Transport hazard class(es) (RID) : 2.1

Danger labels (RID) : 2.1



14.4. Packing group

Packing group (ADR) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

Packing group (ADN) : Not applicable

Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I

Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP02

Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9

Transport category (ADR) : 2

Special provisions for carriage - Packages (ADR) : V14

Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12

Special provisions for carriage - Operation (ADR) : S2



705 UNIVERSAL FAST ADHESIVE ACTIVATOR

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 11/2/2014

Revision date: 1/20/2016

Supersedes: 12/12/2015

Version: 1.1

Tunnel restriction code (ADR) : D

- Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959
Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P207, LP02
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW2
Segregation (IMDG) : SG69
MFAG-No : 126

- Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg
Special provisions (IATA) : A145, A167, A802
ERG code (IATA) : 10L

- Inland waterway transport

Classification code (ADN) : 5F
Special provisions (ADN) : 190, 327, 344, 625
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E0
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01, VE04
Number of blue cones/lights (ADN) : 1

- Rail transport

Classification code (RID) : 5F
Special provisions (RID) : 190, 327, 344, 625
Limited quantities (RID) : 1L
Excepted quantities (RID) : E0
Packing instructions (RID) : P207, LP02
Special packing provisions (RID) : PP87, RR6, L2
Mixed packing provisions (RID) : MP9
Transport category (RID) : 2
Special provisions for carriage – Packages (RID) : W14
Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW12
Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable



705 UNIVERSAL FAST ADHESIVE ACTIVATOR

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 11/2/2014

Revision date: 1/20/2016

Supersedes: 12/12/2015

Version: 1.1

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

VOC content : 89 %

15.1.2. National regulations

Germany

VwVwS Annex reference : Water hazard class (WGK) 2, hazard to waters (Classification according to VwVwS, Annex 4)
12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Petroleum gases, liquefied, Petroleum gas, [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately -40 °C to 80 °C (-40 °F to 176 °F).] is listed
SZW-lijst van mutagene stoffen : Petroleum gases, liquefied, Petroleum gas, [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately -40 °C to 80 °C (-40 °F to 176 °F).] is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : n-hexane is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class III-1
Store unit : 50 liter
Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed
Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1A	Carcinogenicity, Category 1A
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Muta. 1B	Germ cell mutagenicity, Category 1B



705 UNIVERSAL FAST ADHESIVE ACTIVATOR

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 11/2/2014

Revision date: 1/20/2016

Supersedes: 12/12/2015

Version: 1.1

Press. Gas	Gases under pressure
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H229	Pressurised container: May burst if heated
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H361f	Suspected of damaging fertility
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS EU AKFIX

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product